

# PVC CONDUIT

## PVC Conduit



## Australian Standard


Approved AS/NZS2053 & AS/NZS61386



### Heavy Duty Rigid Conduit

- Heavy Duty
- V0 Fire Rated, Self-Extinguishing
- anti-UV material, suit for solar installation
- For use in harsh outdoor environment


Size	Outer Dia (D)	Wall Thickness (E)	Code No.
25	24.7~25	2.5~2.8	EPRC25
32	31.7~32	2.7~3.0	EPRC32



### Heavy Duty Corrugated Conduit

- Heavy Duty
- V0 Fire Rated, Self-Extinguishing
- Anti-UV material, suit for solar installation
- Flexible, for use in harsh outdoor environments.

Spec. mm	A mm	B mm	Length m	Code No.
25	17	25	25	EPCC25-25
25	17	25	50	EPCC25-50




## PVC Conduit Fittings




Male Plain to Screwed Conduit Adaptor

Size	D	d	L	d1	H	Code No.
25	31.8	25	23.2	19.1	40	EPMP25
32	37.3	32.3	29.2	25.7	49.4	EPMP32




Female Plain to Screwed Conduit Adapter

Size	D	d	L	d1	H	Code No.
25	29.19	25	22.7	127.8	36	EPFP25




90° Solid Elbow

Size	D	d	L	R	H	Code No.
25	29.2	25	23.2	38.81	50.06	EPSE25



Conduit Coupling Vent

Size	D	d	L	H	Code No.
25	29.0	25.2	25.0	52.0	EPCV25
32	36.3	32.2	27.7	57.8	EPCV32



EDPM Roof Seal

- Material: EDPM+ALUMINUM
- The EPRS Roof Seal could be applicated as example ventilation discharge pipes, roof poles, sewerage vent pipes signboard or flagpole bases, and so on

Description	Pipe Size	Dimensions	Code
Roof seal	0-35mm	100x100x45mm	EPRS

Conduit Mounting Saddle Zinc Plated

- Manufactured from Steel
- Zinc Plated for Finish and Additional Edge Protection



Description	Strip Width	Packing	Code
25mm-Full	19mm	1000PCS/CTN	EPFS25
32mm-Full	25mm	1000PCS/CTN	EPFS32
25mm-Half	25mm	1000PCS/CTN	EPHS25
32mm-Half	25mm	1000PCS/CTN	EPHS32